Ref. Certif. No.

ES2601-M1-AENOR

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	FIXED GENERAL PURPOSE LUMINAIRE
Name and address of the applicant	ZALUX, S.A. CENTRO EMPRESARIAL MIRALBUENO. AVENIDA MANUEL RODRÍGUEZ AYUSO, 114 PLANTA 1ª LOCAL P-2 50012 ZARAGOZA (Spain
Name and address of the manufacturer	ZALUX, S.A. Avenida ARAGÓN, 54 50230 ALHAMA DE ARAGÓN (Zaragoza - Spain)
Name and address of the factory	SAME AS ABOVE
Note: *When more than one factory, please report on page 2*	☐ Additional Information on page 2
Ratings and principal characteristics	SEE ANNEX
Trademark (if any)	ZALUX
Customer's Testing Facility (CTF) Stage used	---
Model / Type Ref.	SEE ANNEX
Additional information (if necessary may also be reported on page 2)	☒ Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60598-1:2020 IEC 60598-2-1:2020 IEC 60598-2-24:2013 IEC 62262:2002
As shown in the Test Report Ref. No. which forms part of this Certificate	2022110713B1-M1

This CB Test Certificate is issued by the National Certification Body

AENOR CONFÍA S.A.U.
Cl Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2025-02-10

Signature: Rafael GARCÍA MEIRO
CEO

ANNEX TO CB CERTIFICATE Nº ES2601-M1-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

FIXED GENERAL PURPOSE LUMINAIRE

Type reference	Trade mark	Rated voltage and frequency	Nº of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Power supply connection means	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
IBERA 0.6	Zalux	220-240 V~; 0-50/60 Hz	10 - 17 W	LED module (SMD)	IP66; IK08	Terminals	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 35 °C max	IBERA Series; cool, neutral and warm white; 600 mm length
IBERA+ 1.2	Zalux	220-240 V~; 0-50/60 Hz	19 - 30 W	LED module (SMD)	IP66; IK08	Terminals	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 35 °C max	IBERA Series; cool, neutral and warm white; 1200 mm length
IBERA 1.2	Zalux	220-240 V~; 0-50/60 Hz	19 - 30 W	LED module (SMD)	IP66; IK08	Terminals	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 35 °C max	IBERA Series; cool, neutral and warm white; 1200 mm length
IBERA+ 1.5	Zalux	220-240 V~; 0-50/60 Hz	33 - 47 W	LED module (SMD)	IP66; IK08	Terminals	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 35 °C max	IBERA Series; cool, neutral and warm white; 1500 mm length
IBERA 1.5	Zalux	220-240 V~; 0-50/60 Hz	33 - 47 W	LED module (SMD)	IP66; IK08	Terminals	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 35 °C max	IBERA Series; cool, neutral and warm white; 1500 mm length